



Axial Fan  
**UF17PC Series**

Frame/Housing:	Aluminum die-casting
Impeller:	Plastic PBT PC, nylon or metal
Bearing System:	Ball bearing or sleeve bearing
Motor:	Shaded pole or capacitor start-run
Connection:	Lead wire or terminal type
Protection:	Impedance-Protected or Thermally-Protected
Dielectric withstand voltage:	Above 10MΩ, DC500V
Life Expectancy:	Ball bearing: Over 40,000 hr. (at 40°C) Sleeve bearing: Over 15,000 hr. (at 40°C)
Safety Approval:	CUL, CE, TUV, either UL or ETL
Description of Model No.	UF    12    A    (R)    11    B    T    H    N
	1      2      3      4      5      6      7      8      9

	UF17PC11-H	UF17PC23-H
Rated Voltage	115 V	230 V
Frequency	50/60 Hz	50/60 Hz
Input Power	31/31 W	29/29 W
Rated Current	0.26/0.25 A	0.12/0.12 A
Locked Current	0.41/0.43 A	0.19/0.19 A
Speed	2850/3400 RPM	2850/3400 RPM
Maximum Air Flow	5.8/6.4 m3/min.	5.8/6.4 m3/min.
Maximum Air Flow	205/226 CFM	205/226 CFM
Maximum Pressure	16/20 mmH2O	16/20 mmH2O
Maximum Pressure	0.63/0.79 InchH2O	0.63/0.79 InchH2O
Noise	50/55 dB	50/55 dB
Weights	0.82 kg	0.82 kg

SAFETY APPROVAL

